

Eaton PDUMH16HV

Eaton Tripp Lite series metered outlet PDU, 1PH, 1U, IEC-60309, 8 ft cord, 3.7kW, 16A, 208/230V, 10 Outlets (8) C13 (2) C19 TAA



Specifiche generali

PRODUCT NAME	Eaton Tripp Lite series metered outlet PDU
CATALOG NUMBER	PDUMH16HV
UPC	037332182791
PRODUCT LENGTH/DEPTH	6.5 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	17.5 in
PRODUCT WEIGHT	3.9 lb
COMPLIANCES	RoHS CE Marked FCC Class A EAC TAA Compliant
CERTIFICATIONS	RETIE GoST-R NOM IEC 62368-1

Caratteristiche prodotto

FORM FACTOR	1U
PACKAGE CONTENTS	<ul style="list-style-type: none">• Rackmount PDU• Rack mounting brackets• Plug lock inserts• IEC-309 Blue 16A input cord
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
MOUNTING DIRECTION	Horizontal
MATERIAL	Metal
INPUT CONNECTION	IEC-60309 16A BLUE (2P+E)
CORD LENGTH	8.2 ft
AMPERAGE RATING	16A
ELECTRIC CURRENT - MAX	16
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
NUMBER OF OUTPUTS C13	8
NUMBER OF OUTPUTS C19	2
FEATURES	Flex Center
FRONT PANEL LCD DISPLAY	Digital display reports total PDU output current in amps
OUTPUT RECEPTACLES	C13 C19
GROUNDING OPTIONS	Front panel grounding lug
MINIMUM REQUIRED RACK DEPTH	10 in
RECOMMENDED ELECTRICAL SERVICE	Single-phase 16/20A 230/208V service
RECEPTACLES	<ul style="list-style-type: none">• C13• C19
INPUT CORD LENGTH	8.2 ft
PRODUCT FEATURES	TAA Compliant
OPERATING ELEVATION	0-10000 ft. (0-3000 m)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
OUTPUT NOMINAL VOLTAGE	208/230V
RELATIVE HUMIDITY	5% to 95% non-

Risorse

	condensing
FORM FACTORS SUPPORTED	1U rackmount. Includes mounting accessories for 2-4 post racks
OUTPUT CAPACITY DETAILS	3.7kW (230V), 3.3kW (208V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet
STORAGE TEMPERATURE	-22° to 122°F (-30° to 50°C)
PRODUCT HIGHLIGHTS	1U horizontal rackmount; digital current meter Local metered single phase 16A 208/230V PDU TAA Compliant C20 input with IEC-309 Blue 16A input; 2.5m line cord 10 total outlets (8 C13, 2 C19); 6.5 in. / 16.5 cm depth
PDU PLUG TYPE	IEC-60309 16A BLUE (2P+E)
PDU TYPE	Local metered
PDU INPUT VOLTAGE	208
PDU FORM FACTOR	Horizontal (1U)

NOME DEL PROGETTO:

NUMERO DEL PROGETTO:

PREPARATO DA:

DATA:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublino 4, Irlanda
Eaton.com

© 2026 Eaton. Tutti i diritti riservati.

Seguici sui social media per avere informazioni aggiornate sui prodotti e sull'assistenza.

