Caratteristiche



Eaton PDUMV32HV

Eaton Tripp Lite series metered outlet PDU, 1PH, 0U, IEC-60309 input, 10 ft cord, 7.7kW, 32A, 200-240V, 48 Outlets (20) C13 (8) C19

Specifiche generali	
PRODUCT NAME	Eaton Tripp Lite series metered outlet PDU
CATALOG NUMBER	PDUMV32HV
UPC	037332182814
PRODUCT LENGTH/DEPTH	2.52 in
PRODUCT HEIGHT	70 in
PRODUCT WIDTH	2.17 in
PRODUCT WEIGHT	13 lb
COMPLIANCES	CE Marked RoHS FCC Class B
CERTIFICATIONS	RETIE NOM IEC 62368-1

Powering Business Worldwide

Caratteristiche prodotto

FORM FACTOR	0U (Vertical)
PACKAGE CONTENTS	• PDUMV32HV 32A 200-240V 7.7kW Single-Phase Local metered PDU • Plug-lock inserts (8 C20, 40 C13) • Spare installation buttons, 2.9 mm/4.6 mm • Ground screw • Mounting hardware • Owner's Manual
MOUNTING DIRECTION	Vertical
MATERIAL	Metal
INPUT CONNECTION	IEC-60309 32A BLUE (2P+E)
CORD LENGTH	10 ft
AMPERAGE RATING	32A
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
NUMBER OF OUTPUTS C13	40
NUMBER OF OUTPUTS C19	8
FEATURES	Flex Center
FRONT PANEL LCD DISPLAY	Set of two digital current meters report output current in two segments
OUTPUT RECEPTACLES	C19 C13
OVERLOAD PROTECTION	Two 20A circuit breakers protect 24 outlets each
RECOMMENDED ELECTRICAL SERVICE	Single-phase 32A 200-240V service
REPORTED LOAD SEGMENTS	Supports local monitoring of output current for each output load bank; Outlets, circuit breakers and current meters are color-coded and labeled for easy identification (Black: 20A Bank 1 / Gray: 20A Bank 2)
OPERATING ELEVATION	0-3000
OPERATING TEMPERATURE RANGE	32° to 122°F (0° to 50°C)

Risorse

OUTPUT NOMINAL VOLTAGE	200-240V
RELATIVE HUMIDITY	5% to 95% non-condensing
FORM FACTORS SUPPORTED	0u vertical installation in equipment racks, plus under-counter and wallmount
OUTPUT CAPACITY DETAILS	7.7kW (240V), 7.4kW (230V), 7kW (220V), 6.7kW (208V), 6.4kW (200V) / 32A total capacity; 16A max per breakered outlet bank; 16A max per C19 outlet; 10A max per C13 outlet
STORAGE TEMPERATURE	-22° to 140°F (-30° to 60°C)
PRODUCT HIGHLIGHTS	Ideal for server rooms, network closets and data centers IEC-309 32A blue input plug with 10-ft. (3.05 m) cord Dedicated 20A circuit breakers protect output Dual load banks with 24 outlets each (4 C19 and 20 C13) Ready for immediate toolless 0U installation
PDU TYPE	Local metered
PDU INPUT VOLTAGE	200
PDU FORM FACTOR	Vertical (0U)

NOME DEL PROGETTO:	
NUMERO DEL PROGETTO:	
PREPARATO DA:	
DATA:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublino 4, Irlanda
Eaton.com

© 2026 Eaton. Tutti i diritti riservati.

Seguici sui social media per avere informazioni aggiornate sui prodotti e sull'assistenza.