

## XS32

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		XS32
EAN		5027590515337
Product Length/Depth		80 millimetre
Product height		27 millimetre
Product width		27 millimetre
Product weight		66.5 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC 60269 EAC BS88
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		32 A
Voltage rating		440 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		XS
Fitted with:		Offset bladed tags
Connection		Blade end
Suitable for		SC125 Safeclip fuse holder

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F3
Type of current		AC
Rated voltage AC	V	440
Rated voltage DC	V	
Rated current	A	32
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		
Centre-to-centre distance of connections	mm	