Especificações







Eaton 138258

Eaton Moeller® series PKE65 Circuit-breaker, Basic device with standard knob, Electronic, 65 A, Without overload releases

Especificações gerais	
PRODUCT NAME	Eaton Moeller® series PKE Motor-protective circuit-breaker
CATALOG NUMBER	138258
EAN	4015081350384
PRODUCT LENGTH/DEPTH	187 mm
PRODUCT HEIGHT	162 mm
PRODUCT WIDTH	55 mm
PRODUCT WEIGHT	1.231 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Std. C22.2 No. 14-10 IEC 60947-4-1 UL 508 VDE UL File No.: E36332 CE IEC/EN 60947 UL CSA CSA-C22.2 No. 60947-4-1-14 VDE 0660 CSA File No.: 165628 UL 60947-4-1 IEC/EN 60947-4-1 UL Category Control No.: NLRV CSA Class No.: 3211-05
MODEL CODE	PKE65

Powering Business Worldwide

Condições ambientais, mecânicas

SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Condições meteorológicas

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Comunicação

CONNECTION	Screw terminals

Verificação do design

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS	Meets the product standard's requirements.

TO NORMAL HEAT	
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	12.9 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	4.3 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	65 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Classificação elétrica

RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RATED OPERATIONAL CURRENT (IE)	65 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
RATED UNINTERRUPTED CURRENT (IU)	65 A

Features & functions

ACTUATOR TYPE	Turn button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FITTED WITH:	Standard knob
FUNCTIONS	Line and cable protection Motor protection Motor protection for heavy starting duty System protection
NUMBER OF POLES	Three-pole

Informações gerais

DEGREE OF PROTECTION	IP20 Terminals: IP00
LIFESPAN, ELECTRICAL	50,000 operations (at 400V, AC-3)
LIFESPAN, MECHANICAL	30,000 Operations (Main conducting paths)
OPERATING FREQUENCY	60 Operations/h
OVERLOAD RELEASE CURRENT SETTING - MAX	0 A
OVERLOAD RELEASE CURRENT SETTING - MIN	0 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SUITABLE FOR	Also motors with efficiency class IE3
TEMPERATURE COMPENSATION	-5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range

Classificação de curto-circuito

SHORT-CIRCUIT RELEASE	Basic device fixed 15.5 x Iu, Trip Blocks ± 20% tolerance, Trip blocks

Capacidade de comutação

SWITCHING CAPACITY	65 A, AC-3 up to 690 V

Capacidades dos terminais

STRIPPING LENGTH (MAIN CABLE)	14 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 25) mm², ferrule to DIN 46228 1 x (0.75 - 35) mm², ferrule to DIN 46228
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 16) mm² 2 x (0.75 - 16) mm²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	14 - 2
TIGHTENING TORQUE	1 Nm, Screw terminals, Control circuit cables 3.3 Nm, Screw terminals, Main cable

Recursos	
BROCHURAS	eaton-motor-protective-circuit-breaker-pke-and-communication-modul-pke-brochure-w12107613en-en-us.pdf
CHARACTERISTIC CURVE	eaton-manual-motor-starters-pke65-characteristic-curve-002.eps eaton-manual-motor-starters-pke65-characteristic-curve-005.eps eaton-manual-motor-starters-pke65-characteristic-curve-004.eps
DECLARATIONS OF CONFORMITY	eaton-motor-protective-circuit-breaker-declaration-of-conformity-eu250696en.pdf eaton-motor-protective-circuit-breaker-declaration-of-conformity-uk251179en.pdf
DESENHOS	eaton-manual-motor-starters-pke65-dimensions.eps eaton-manual-motor-starters-mounting-3d-drawing.eps eaton-general-ie-ready-dilm-contactor-standards.eps eaton-manual-motor-starters-pke65-mccb-3d-drawing.eps
ECAD MODEL	ETN.138258.edz
INSTRUÇÕES DE INSTALAÇÃO	IL034013ZU eaton-motor-protective-circuit-breaker-pke-il03402019z.pdf
MCAD MODEL	pke65.stp eaton-breakers-mcad-drawings-pke65.dwg
NOTAS DE VENDAS	eaton-pke-modbus-rtu-modul-flyer-fl034008en-en-us.pdf

VÍDEOS DE INSTALAÇÃO	Video Motor Protective Circuit Breaker PKE

NOME DO PROJETO:
NÚMERO DO PROJETO:
PREPARADO POR:
DATA:

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2026 Eaton. Todos os direitos reservados.

Siga-nos nas redes sociais para obter as informações mais recentes sobre os nossos produtos e suporte.