




**Wall fixing bracket**

**Part no.** +W-MCS  
**Catalog No.** 001631  
**Alternate Catalog No.** -

**Delivery program**

|                |  |  |  |
|----------------|--|--|--|
| Product range  |  |  | Accessories                              |
| Basic function |  |  | Wall fixing bracket                      |
|                |  |  | Article no. for ordering with basic unit |
| For use with   |  |  | MCS, MCSN                                |



**Notes**

Wall mounting bracket can be rotated to right or left by 90°

**Notes** Article no. for ordering with basic unit

**Design verification as per IEC/EN 61439**

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |

**Technical data ETIM 7.0**

|   |  |  |            |
|---|--|--|------------|
| Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)   |  |  |            |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013]) |  |  |            |
| Type of accessory   |  |  | Wall mount |

**Approvals**

|                             |  |  |                   |
|-----------------------------|--|--|-------------------|
| Product Standards           |  |  | CSA-CC22.2 No. 14 |
| CSA File No.                |  |  | 12528             |
| CSA Class No.               |  |  | 3211-06           |
| North America Certification |  |  | CSA certified     |

## Dimensions

