

Busbar assembly, 3p, in=250A

Part no. SE-RS-I43
044005
EL Number 2502205
(Norway)

| | |
|---------------------------|---|
| Product name | Eaton xEnergy Safety Ci busbar assembly RS |
| Part no. | SE-RS-I43 |
| EAN | 4015080440055 |
| Product Length/Depth | 100 millimetre |
| Product height | 250 millimetre |
| Product width | 375 millimetre |
| Product weight | 1.104 kilogram |
| Compliances | RoHS conform |
| Product Tradename | xEnergy Safety Ci |
| Product Type | Accessories |
| Product Sub Type | Busbar assembly RS |
| Type | Modular busbar system Prepared enclosures xEnergy Safety Ci |
| Accessory/spare part type | Busbar assemblies |
| Number of poles | Three-pole |
| Current rating - max | 250 A |
| Unit type | Modular system |
| Busbar distance | 50 mm |
| Functions | For fitting busbar mounting fuse bases Prepared enclosure 3 pole, for 250 A rated operational current |
| Suitable for | Fitting busbar mounting fuse bases 3 pole, for 250 A rated operational current |
| Used with | C143... Modular busbar system xEnergy Safety Ci Prepared enclosures |

Technical data ETIM 8.0

| | | | |
|--|--|----|-----|
| Energy distribution systems (EG000015) / Busbar support (EC001166) | | | |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar support (ecl@ss10.0.1-27-40-06-07 [AC0377011]) | | | |
| Number of poles | | | 3 |
| Max. rated current | | A | 250 |
| Busbar distance | | mm | 50 |