

Copper busbar, 40x10x1500mm, untreated



Part no. **CU40X10**  
 Catalog No. **063076**

**Delivery program**

Product range			60 mm system
Accessories			Flat copper bars
Single unit/Complete unit			Modular system
Description			Flat copper busbars
Surface finish			Untreated
Rated operational current	I <sub>e</sub>	A	850
Length		mm	1500
For use with			SH1603/4
Cu factor		kg	5,34
<b>Copper busbars</b>			
Width		mm	40
Height		mm	10
Material			Copper, non-insulated
<b>Notes</b>			
Calculating material allowance → General information chapter			
Selecting the busbar cross-section and the device to be used → Engineering chapter			

**Technical data**

**Material characteristics**

Material			Copper, non-insulated
Surface finish			Untreated

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Busbar (EC001522)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar (low-voltage switching technology) (ec1@ss10.0.1-27-37-03-03 [ACN949011])			
Rated current I <sub>n</sub>		A	800
Model			Flat
Length		mm	1500
Width		mm	40
Height		mm	10
Flexible			No
Surface protection			Untreated