



Busbar support, N, PE, for CI enclosure, hxD=20x5(10, 15)mm

Part no. SH0632

Catalog No. 067739

EL-Nummer (Norway) 2502276

Delivery program

Product range			xEnergy Safety Ci
Basic function			Prepared enclosures
Product function			Modular busbar system
Accessories			PE/N busbar supports
Single unit/Complete unit			Modular system
Function			For relocating PE/N bars from the busbar enclosure to the terminal compartment (from floor standing distribution boards)
Rated operational current	I_e	A	250 400 630
Dimensions		mm	20 x 5 20 x 10 20 x 15

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Busbar support (EC001166)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar support (ecl@ss10.0.1-27-40-06-07 [AC0377011])			
Number of poles			2
Max. rated current		A	630
Busbar distance		mm	50

Additional product information (links)

allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&model certification xEnergy Safety Ci	
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&Save time – we assist you with expert pre-assembly	
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&product information xEnergy Safety Ci	
tool for calculating the power loss for switching device combinations	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm
configurator - xEnergy family	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm