

**Shunt release (for power circuit breaker), 120 V 60 Hz, Standard voltage, AC, Screw terminals, For use with: Shunt release PKZ0(4), PKE**



Powering Business Worldwide™

**Part no. A-PKZ0(120V60HZ)  
073195**

Product name	Eaton Moeller® series A-PKZ0 Accessory Shunt release
Part no.	A-PKZ0(120V60HZ)
EAN	4015080731955
Product Length/Depth	68 millimetre
Product height	90 millimetre
Product width	24 millimetre
Product weight	0.131 kilogram
Certifications	CSA CSA File No.: 165628 UL File No.: E36332 UL Category Control No.: NLRV IEC/EN 60947-4-1 UL 508 CE UL CSA Class No.: 3211-05 CSA-C22.2 No. 14
Product Tradename	A-PKZ0
Product Type	Accessory
Product Sub Type	Shunt release
Catalog Notes	Cannot be combined with U-PKZ0 undervoltage release Cannot be combined with undervoltage release U-PKZ0
Electric connection type	Screw connection
Product category	Accessories
Suitable for	Motor safety switch
Used with	Motor protective circuit-breaker
Voltage type	AC
Mounting position	Can be fitted to left side of the motor protection switch
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Terminal capacity (solid/flexible with ferrule)	1 x (0.75 - 2.5) mm <sup>2</sup> 2 x (0.75 - 2.5) mm <sup>2</sup>
Terminal capacity (solid/stranded AWG)	2 x (18 - 14) 1 x (18 - 14)
Operational voltage	0.7 - 1.1 x Us (AC) 0.7 - 1.1 x Us (alternating voltage) 0.7 - 1.1 x Us (DC)
Rated operational voltage (Ue) at AC - min	42 V
Rated operational voltage (Ue) at AC - max	480 V
Rated operational voltage (Ue) at DC - min	24 V
Rated operational voltage (Ue) at DC - max	250 V
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	120 V
Rated control supply voltage (Us) at AC, 60 Hz - max	120 V
Rated control supply voltage (Us) at DC - min	0 V

Rated control supply voltage (Us) at DC - max		0 V
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		0
Power consumption, pick-up, 50 Hz		5 VA, Pull-in power, Coil in a cold state and 1.0 x Us
Power consumption, pick-up, 60 Hz		5 VA, Pull-in power, Coil in a cold state and 1.0 x Us
Power consumption, sealing, 50 Hz		3 VA, Coil in a cold state and 1.0 x Us
Power consumption, sealing, 60 Hz		3 VA, Coil in a cold state and 1.0 x Us
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0.5 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip (ecl@ss10.0.1-27-37-04-18 [AKF016013])		
Rated control supply voltage Us at AC 50HZ	V	0 - 0
Rated control supply voltage Us at AC 60HZ	V	120 - 120
Rated control supply voltage Us at DC	V	0 - 0
Voltage type for actuating		AC
Initial value of the undelayed short-circuit release - setting range	A	0
End value adjustment range undelayed short-circuit release	A	0
Type of electric connection		Screw connection
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Suitable for power circuit breaker		No
Suitable for off-load switch		No

Suitable for motor safety switch		Yes
Suitable for overload relay		No