



Indicator light, green, 500V neon lamp

L-PKZ0-GN(500V)

082156

XTPAXILGC

EATON Powering Business Worldwide^{*}

Part no. Catalog No. Alternate Catalog No.

Delivery program Product range Accessories Accessories Indicator lights Colour green v 415 - 500 Voltage Voltage Us ٧ 415 - 500 CI-K2-PKZ0-... CI-K4-PKZ4 CI-PKZ0(1) For use with E-PKZ0(1)

Design verification as per IEC/EN 61439

| Design verification as per IEC/EN 61439 | | | |
|--|-------------------|----|--|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | In | Α | 0 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P _{vs} | W | 0.46 |
| Heat dissipation capacity | P _{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 55 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Please enquire |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |

| 10.10 Temperature rise | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
|-------------------------------------|--|
| 10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Indicator light complete (EC000272)

| Electric engineering, automation, process control engineering / Low-voltage swi | itch technology / (| Command | and alarm device / Indicator light complete (ecl@ss10.0.1-27-37-12-23 [AKF041014]) |
|---|---------------------|---------|--|
| Number of indicator lights | | | 5 |
| Colour lens | | | Green |
| Type of lamp socket | | | Other |
| With light source | | | Yes |
| Rated operating voltage Ue | | V | 415 - 500 |
| Voltage type | | | AC/DC |
| Type of electric connection | | | Flat plug-in connection |
| Construction type lens | | | Rectangular |
| Type of lens | | | Flat |
| Hole diameter | | mm | 16 |
| Width opening | | mm | 0 |
| Height opening | | mm | 0 |
| With front ring | | | No |
| Material front ring | | | Plastic |
| Colour front ring | | | Other |
| Degree of protection (IP) | | | IP65 |
| Degree of protection (NEMA) | | | Other |

Approvals

Specially designed for North America

No

Additional product information (links)

| IL03402035Z (AWA1210-0554) Indicator light for motor-protective circuit-breaker | | | | |
|---|--|--|--|--|
| IL03402035Z (AWA1210-0554) Indicator light for motor-protective circuit-breaker | https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03402035Z2021_08.pdf | | | |
| Motor starters and "Special Purpose Ratings" for the North American market | http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf | | | |
| Busbar Component Adapters for modern Industrial control panels | http://www.moeller.net/binary/ver_techpapers/ver960en.pdf | | | |