



Screen winding, for STZ transformer up to 1.6KVA

Part no. **+W1,8**
 Catalog No. **082270**
 Alternate Catalog No. **-**

Delivery program

| | | |
|----------------|--|--------------------|
| Product range | | Accessories |
| Accessories | | Shielding winding |
| For use with | | STZ0.06 ... STZ1.6 |
| Cu factor 0,00 | | |

Technical data

General

| | | |
|---------------------|--|----------|
| Ambient temperature | | -25 - 40 |
|---------------------|--|----------|

Characteristics

| | | |
|-------------------|--|-----|
| Insulation class | | B/F |
| Separate windings | | ● |

Design verification as per IEC/EN 61439

| | | |
|--|----|-----|
| Technical data for design verification | | |
| Operating ambient temperature min. | °C | -25 |
| Operating ambient temperature max. | °C | 40 |

Technical data ETIM 7.0

| | | |
|---|--|-------|
| Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013]) | | |
| Type of accessory | | Other |

Approvals

| | | |
|-----------------------------|--|-----------------------------------|
| North America Certification | | UL/CSA certification not required |
|-----------------------------|--|-----------------------------------|