




On-Off switch, T5, 100 A, rear mounting, 10 contact unit(s), 20-pole, with black thumb grip and front plate



Part no. T5-10-8356/Z
Catalog No. 097097

Delivery program

Product range		On-Off switch																																																																																																																											
Part group reference		T5																																																																																																																											
		with black thumb grip and front plate																																																																																																																											
Number of poles		20-pole																																																																																																																											
Degree of Protection		Front IP65																																																																																																																											
Design		rear mounting																																																																																																																											
Contact sequence		<table><tr><td></td><td>0</td><td>1</td></tr><tr><td>1 o</td><td></td><td>X</td></tr><tr><td>2 o</td><td></td><td>X</td></tr><tr><td>3 o</td><td></td><td>X</td></tr><tr><td>4 o</td><td></td><td>X</td></tr><tr><td>5 o</td><td></td><td>X</td></tr><tr><td>6 o</td><td></td><td>X</td></tr><tr><td>7 o</td><td></td><td>X</td></tr><tr><td>8 o</td><td></td><td>X</td></tr><tr><td>9 o</td><td></td><td>X</td></tr><tr><td>10 o</td><td></td><td>X</td></tr><tr><td>11 o</td><td></td><td>X</td></tr><tr><td>12 o</td><td></td><td>X</td></tr><tr><td>13 o</td><td></td><td>X</td></tr><tr><td>14 o</td><td></td><td>X</td></tr><tr><td>15 o</td><td></td><td>X</td></tr><tr><td>16 o</td><td></td><td>X</td></tr><tr><td>17 o</td><td></td><td>X</td></tr><tr><td>18 o</td><td></td><td>X</td></tr><tr><td>19 o</td><td></td><td>X</td></tr><tr><td>20 o</td><td></td><td>X</td></tr><tr><td>21 o</td><td></td><td>X</td></tr><tr><td>22 o</td><td></td><td>X</td></tr><tr><td>23 o</td><td></td><td>X</td></tr><tr><td>24 o</td><td></td><td>X</td></tr><tr><td>25 o</td><td></td><td>X</td></tr><tr><td>26 o</td><td></td><td>X</td></tr><tr><td>27 o</td><td></td><td>X</td></tr><tr><td>28 o</td><td></td><td>X</td></tr><tr><td>29 o</td><td></td><td>X</td></tr><tr><td>30 o</td><td></td><td>X</td></tr><tr><td>31 o</td><td></td><td>X</td></tr><tr><td>32 o</td><td></td><td>X</td></tr><tr><td>33 o</td><td></td><td>X</td></tr><tr><td>34 o</td><td></td><td>X</td></tr><tr><td>35 o</td><td></td><td>X</td></tr><tr><td>36 o</td><td></td><td>X</td></tr><tr><td>37 o</td><td></td><td>X</td></tr><tr><td>38 o</td><td></td><td>X</td></tr><tr><td>39 o</td><td></td><td>X</td></tr><tr><td>40 o</td><td></td><td>X</td></tr></table>		0	1	1 o		X	2 o		X	3 o		X	4 o		X	5 o		X	6 o		X	7 o		X	8 o		X	9 o		X	10 o		X	11 o		X	12 o		X	13 o		X	14 o		X	15 o		X	16 o		X	17 o		X	18 o		X	19 o		X	20 o		X	21 o		X	22 o		X	23 o		X	24 o		X	25 o		X	26 o		X	27 o		X	28 o		X	29 o		X	30 o		X	31 o		X	32 o		X	33 o		X	34 o		X	35 o		X	36 o		X	37 o		X	38 o		X	39 o		X	40 o		X
	0	1																																																																																																																											
1 o		X																																																																																																																											
2 o		X																																																																																																																											
3 o		X																																																																																																																											
4 o		X																																																																																																																											
5 o		X																																																																																																																											
6 o		X																																																																																																																											
7 o		X																																																																																																																											
8 o		X																																																																																																																											
9 o		X																																																																																																																											
10 o		X																																																																																																																											
11 o		X																																																																																																																											
12 o		X																																																																																																																											
13 o		X																																																																																																																											
14 o		X																																																																																																																											
15 o		X																																																																																																																											
16 o		X																																																																																																																											
17 o		X																																																																																																																											
18 o		X																																																																																																																											
19 o		X																																																																																																																											
20 o		X																																																																																																																											
21 o		X																																																																																																																											
22 o		X																																																																																																																											
23 o		X																																																																																																																											
24 o		X																																																																																																																											
25 o		X																																																																																																																											
26 o		X																																																																																																																											
27 o		X																																																																																																																											
28 o		X																																																																																																																											
29 o		X																																																																																																																											
30 o		X																																																																																																																											
31 o		X																																																																																																																											
32 o		X																																																																																																																											
33 o		X																																																																																																																											
34 o		X																																																																																																																											
35 o		X																																																																																																																											
36 o		X																																																																																																																											
37 o		X																																																																																																																											
38 o		X																																																																																																																											
39 o		X																																																																																																																											
40 o		X																																																																																																																											

Switching angle		°	90
Switching performance			maintained
Design number			8356
Front plate no.			 FS 908
front plate			0-1
Motor rating AC-23A, 50 - 60 Hz			
400 V	P	kW	55
Rated uninterrupted current	I _u	A	100
Note on rated uninterrupted current I _u			Rated uninterrupted current I _u is specified for max. cross-section.
Number of contact units		contact unit(s)	10

Technical data

General

Standards			IEC/EN 60947, VDE 0660, IEC/EN 60204 Switch-disconnector according to IEC/EN 60947-3
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature			
Open		°C	-25 - +50
Enclosed		°C	-25 - +40
Overvoltage category/pollution degree			III/3
Rated impulse withstand voltage	U _{imp}	V AC	6000
Mechanical shock resistance		g	15
Mounting position			As required

Contacts

Mechanical variables			
Number of poles			20-pole
Electrical characteristics			
Rated operational voltage	U _e	V AC	690
Rated uninterrupted current	I _u	A	100
Note on rated uninterrupted current I _u			Rated uninterrupted current I _u is specified for max. cross-section.
Load rating with intermittent operation, class 12			
AB 25 % DF		x I _e	2
AB 40 % DF		x I _e	1.6
AB 60 % DF		x I _e	1.3
Short-circuit rating			
Fuse		A gG/gL	100
Rated short-time withstand current (1 s current)	I _{cw}	A _{rms}	1700
Note on rated short-time withstand current I _{cw}			Current for a time of 1 second
Rated conditional short-circuit current	I _q	kA	2

Switching capacity

cos φ rated making capacity as per IEC 60947-3		A	950
Rated breaking capacity cos φ to IEC 60947-3		A	
230 V		A	760
400/415 V		A	740
500 V		A	590
690 V		A	420
Safe isolation to EN 61140			

between the contacts		V AC	440
Current heat loss per contact at I _e		W	7.5
Current heat loss per auxiliary circuit at I _e (AC-15/230 V)		CO	7.5
Lifespan, mechanical	Operations	x 10 ⁶	> 0.5
Maximum operating frequency	Operations/h		1200
AC			
AC-3			
Rating, motor load switch	P	kW	
220 V 230 V	P	kW	22
230 V Star-delta	P	kW	30
400 V 415 V	P	kW	30
400 V Star-delta	P	kW	45
500 V	P	kW	30
500 V Star-delta	P	kW	45
690 V	P	kW	15
690 V Star-delta	P	kW	22
Rated operational current motor load switch			
230 V	I _e	A	71
230 V star-delta	I _e	A	100
400V 415 V	I _e	A	55
400 V star-delta	I _e	A	95.3
500 V	I _e	A	44
500 V star-delta	I _e	A	76.2
690 V	I _e	A	17
690 V star-delta	I _e	A	29.4
AC-23A			
Motor rating AC-23A, 50 - 60 Hz	P	kW	
230 V	P	kW	30
400 V 415 V	P	kW	55
500 V	P	kW	37
690 V	P	kW	30
Rated operational current motor load switch			
230 V	I _e	A	100
400 V 415 V	I _e	A	100
500 V	I _e	A	55
690 V	I _e	A	32
DC			
DC-1, Load-break switches L/R = 1 ms			
Rated operational current	I _e	A	80
Voltage per contact pair in series		V	60
Control circuit reliability at 24 V DC, 10 mA	Fault probability	H _F	< 10 ⁻⁵ , < 1 failure in 100,000 switching operations

Terminal capacities

Solid or stranded		mm ²	1 x (2,5 - 35) 2 x (2,5 - 16)
Flexible with ferrules to DIN 46228		mm ²	1 x (1 - 25) 2 x (1.5 - 10)
Terminal screw			M6
Tightening torque for terminal screw		Nm	4

Technical safety parameters:

Notes			B10 _d values as per EN ISO 13849-1, table C1
--------------	--	--	---

Rating data for approved types

Contacts			
Rated operational voltage	U _e	V AC	600
Rated uninterrupted current max.			
Main conducting paths			

General use	A	65
Terminal capacity		
Terminal screw		M6

Design verification as per IEC/EN 61439


Technical data for design verification			
Rated operational current for specified heat dissipation	I _n	A	100
Heat dissipation per pole, current-dependent	P _{vid}	W	7.5
Equipment heat dissipation, current-dependent	P _{vid}	W	0
Static heat dissipation, non-current-dependent	P _{vs}	W	0
Heat dissipation capacity	P _{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	50
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			UV resistance only in connection with protective shield.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss10.0.1-27-37-14-03 [AKF060013])			
Version as main switch			No
Version as maintenance-/service switch			No
Version as safety switch			No
Version as emergency stop installation			No
Version as reversing switch			No
Number of switches			1
Max. rated operation voltage U _e AC		V	690
Rated operating voltage		V	690 - 690
Rated permanent current I _u		A	100
Rated permanent current at AC-23, 400 V		A	100

Rated permanent current at AC-21, 400 V	A	100
Rated operation power at AC-3, 400 V	kW	30
Rated short-time withstand current I _{cw}	kA	1.7
Rated operation power at AC-23, 400 V	kW	55
Switching power at 400 V	kW	55
Conditioned rated short-circuit current I _q	kA	2
Number of poles		20
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
Motor drive optional		No
Motor drive integrated		No
Voltage release optional		No
Device construction		Built-in device fixed built-in technique
Suitable for ground mounting		Yes
Suitable for front mounting 4-hole		No
Suitable for front mounting centre		No
Suitable for distribution board installation		No
Suitable for intermediate mounting		Yes
Colour control element		Black
Type of control element		Door coupling rotary drive
Interlockable		No
Type of electrical connection of main circuit		Screw connection
Degree of protection (IP), front side		IP65
Degree of protection (NEMA)		Other

Dimensions



Additional product information (links)

Display flip catalog page.	http://ecat.moeller.net/flip-cat/?edition=K115A&startpage=130
Technical overview cam switch, switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.2
System overview cam switch T	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.4
System overview switch-disconnector P	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.6
Key to part numbers Cam switch	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Key to part numbers Switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Switches for ATEX	http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html