



Block busbar 2Ph., 12HP, for FAZ-NA, FAZ-RT

Part no. Z-SV/UL-16/2P-2TE/12
Catalog No. 104896

Delivery program

| | | |
|----------------------------|--|--|
| Basic function | | Busbar |
| Basic function accessories | | Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker |
| Application | | Switchgear for industrial and advanced commercial applications |
| Busbar type | | 2 phase |
| Product range | | Z-SV |

Technical data ETIM 7.0

| | | | |
|--|--|-----------------|-----|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011]) | | | |
| Number of phases | | | 2 |
| Number of poles | | | 2 |
| Suitable for number of devices | | | 0 |
| Pitch dimensions | | mm | 0 |
| Cross section | | mm ² | 16 |
| Length | | mm | 210 |
| Number of modular spacings | | | 2 |
| Rated permanent current I _u | | A | 0 |
| Type of electric connection | | | Pin |
| Insulated | | | Yes |
| Rated surge voltage | | kV | 9.5 |
| Conditioned rated short-circuit current I _q | | kA | 0 |
| Max. rated operation voltage U _e | | V | 690 |
| Rated short-time withstand current I _{cw} | | kA | 0 |
| Suitable for devices with N-busbar | | | No |
| Suitable for devices with auxiliary switch | | | No |

Approvals

| | | |
|--------------------------------------|--|--|
| Product Standards | | IEC/EN 60898; UL 489; CE marking |
| UL File No. | | E257181 |
| UL Category Control No. | | NMTR2, DIHS2 |
| CSA File No. | | - |
| CSA Class No. | | - |
| North America Certification | | UL recognized |
| Specially designed for North America | | Yes, large creepage and creepage distances |
| Suitable for | | Feeder Circuit, Branch Circuit |
| Max. Voltage Rating | | Refer to main components FAZ, FAZ-NA, FAZ-RT |
| Degree of Protection | | IEC: IP20, UL/CSA Type: - |