



Block busbar 3Ph., 18HP, for FAZ-NA, FAZ-RT



Part no. Z-SV/UL-16/3P-3TE/18
Catalog No. 104900

EL-Nummer (Norway) 0001695389

Delivery program

Basic function		Busbar
Basic function accessories		Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker
Application		Switchgear for industrial and advanced commercial applications
Busbar type		Three-phase
Product range		Z-SV

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ec:ss10.0.1-27-37-13-06 [ACN992011])		
Number of phases		3
Number of poles		3
Suitable for number of devices		0
Pitch dimensions	mm	0
Cross section	mm ²	16
Length	mm	315
Number of modular spacings		3
Rated permanent current I _u	A	0
Type of electric connection		Pin
Insulated		Yes
Rated surge voltage	kV	9.5
Conditioned rated short-circuit current I _q	kA	0
Max. rated operation voltage U _e	V	690
Rated short-time withstand current I _{cw}	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		No

Approvals

Product Standards		IEC/EN 60898; UL 489; CE marking
UL File No.		E257181
UL Category Control No.		NMTR2, DIHS2
CSA File No.		-
CSA Class No.		-
North America Certification		UL recognized
Specially designed for North America		Yes, large creepage and creepage distances
Suitable for		Feeder Circuit, Branch Circuit
Max. Voltage Rating		Refer to main components FAZ, FAZ-NA, FAZ-RT
Degree of Protection		IEC: IP20, UL/CSA Type: -