



Shroud section for top and bottom, B=1100mm, for 3p

Part no. BBC-CS2-T/B
Catalog No. 107181

EL-Nummer 2465019
(Norway)

Delivery program

Product range		60 mm system
Basic function		System covers
Subrange		System covers, modular
Material		Silicon free, chlorine free
Self-extinguishing		to UL 94
Temperature resistant		to 120°C
Pole		3
Description		Shroud profile, top/bottom
Length	mm	1100

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Accessories for busbars (EC002270)		
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar (accessories) (ecl@ss10.0.1-27-40-06-36 [AC0563011])		
Type of accessory		Contact protection rail

Approvals

Product Standards		UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.		E300273
UL Category Control No.		NMTR, NMTR7
CSA File No.		236217
CSA Class No.		3211-37
North America Certification		UL listed, CSA certified
Conditions of Acceptability		Refer to approbation report
Specially designed for North America		No
Suitable for		Feeder circuits
Current Limiting Circuit-Breaker		Refer to approbation report
Max. Voltage Rating		600 V AC
Degree of Protection		Feeder circuits

Dimensions

