



Air fuse-link, medium voltage, 25 A, AC 12 kV, 40 kA, BS TA3, 461 x 50.8 mm, back-up, BS, with striker

Part no. 12KV 25AMP 2" 'C' AIR FUSE
Catalog No. 12BDGHC25

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Air fuse-link
Field of application			medium voltage
Rated current	I	A	25
Rated voltage			AC 12 kV
Construction size			BS TA3
Size			461 x 50.8 mm
Utilization category			back-up
Status indicator			with striker
Breaking Capacity		kA	40
usable for size/applications			protection of primary side transformers used in fuse switch combination units, fuse bases and fuse switches
Standard/Approval			BS
Shape			cylindrical offset bolted tags
Standards/Regulations			BS2962-1

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	25
Rated voltage		kV	12
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	40
Utilization category			Other
Application			Primary side transformer protection
Length		mm	461
Diameter		mm	51
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			British Standard
Release characteristic			Other
Installation technique			Air

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf
-------------------------	---