



**Conductor connection terminal M8 for 10mm**

**Part no.** AKU-M8/10  
**Catalog No.** 138362

**Delivery program**

Product range			60 mm system 185 mm system Compact system
Basic function			Connections
Subrange			Universal conductor connection terminals
Description			With integrated retaining spring, open terminal chamber and captive terminal screw
Terminal area W x H		mm	M8 x 8 Bolzen
Width		mm	30
Rated operational current	$I_e$	A	490
conductor			Cable lugs M8
For use with			All 10 mm thick flat busbars Double T profile

**Notes**

○ round conductor, solid

⊗ Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

⊙ Section conductor, solid

Sector conductor, stranded

# CU band

■ CU busbar

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])			
Busbar thickness		mm	10 - 10
Busbar width		mm	0 - 0
Suitable for			Flat rail
Width clamp		mm	30
Max. conductor cross section		mm <sup>2</sup>	0
Max. rated operation current $I_e$		A	490
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			No
Suitable for strip conductor connection			No