



Connection terminal 95-300 mm<sup>2</sup>

Part no. **AK300**  
 Catalog No. **138363**

### Delivery program

Product range			60 mm system
Basic function			Connections
Subrange			Terminals
Description			A cable block is used to connect the conductor to the busbar
Width		mm	48
Rated operational current conductor	$I_e$	A	630
For use with			95 - 300 mm <sup>2</sup>
For use with			30 x 10
For use with			Double T profile Triple T profile

**Notes**

- round conductor, solid
- Flexible, round conductor with correctly crimped ferrule
- Round conductor, stranded
- Section conductor, solid
- Sector conductor, stranded
- # CU band
- CU busbar

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])			
Busbar thickness		mm	10 - 10
Busbar width		mm	30 - 30
Suitable for			T-rail
Width clamp		mm	48
Max. conductor cross section		mm <sup>2</sup>	300
Max. rated operation current $I_e$		A	630
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			No
Suitable for strip conductor connection			Yes