



**Busbar adapter, 4p, for NZM2, 250A, UL508**

**Part no. NZM2-4-XAD250**

**Catalog No. 138388**

**EL-Nummer (Norway) 1718009**

### Delivery program

Product range			60 mm system
Basic function			Busbar adapters for NZM
Subrange			Component adapter for circuit-breakers and switch-disconnectors
Function			For surface mounting on flat copper busbars 12 – 30 x 5 – 10, double T and triple T profile
Rated operational voltage	$U_e$	V AC	690
Temperature resistant			to 120°C
Self-extinguishing			to UL 94
Track resistance			CTI 200
Number of poles			4 pole
Rated operational current	$I_e$	A	250
Adapter width		mm	140
For use with			NZM2-4, PN2-4, N2-4
Cu factor		kg	0,67

**Notes**

Connection to the system possible at top via connection on rear with (+)NZM2-4-XKR4...

Mounting using clamp and screw fixing.

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecI@ss10.0.1-27-37-03-04 [ACN951011])			
Mounting rail armament			None
Type of electric connection			Other
Rated current $I_n$		A	250
Min. busbar thickness		mm	5
Max. busbar thickness		mm	10
Width of the adapter		mm	140
Rail width		mm	30
Busbar distance		mm	60

## Dimensions

