



Busbar adapter, 4p, for NZM3, 630A, UL508

Part no. NZM3-4-XAD630

Catalog No. 138389

EL-Nummer (Norway) 1718010

Delivery program

Product range			60 mm system
Basic function			Busbar adapters for NZM
Subrange			Component adapter for circuit-breakers and switch-disconnectors
Function			For surface mounting on flat copper busbars 12 – 30 x 5 – 10, double T and triple T profile
Rated operational voltage	U_e	V AC	690
Temperature resistant			to 120°C
Self-extinguishing			to UL 94
Track resistance			CTI 200
Number of poles			4 pole
Rated operational current	I_e	A	630
Adapter width		mm	185
For use with			NZM3-4, PN3-4, N3-4
Cu factor		kg	2,16

Notes

Connection to the system possible at top via connection on rear with (+)NZM3-4-XKR13...

Mounting using clamp and screw fixing.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ec@ss10.0.1-27-37-03-04 [ACN951011])

Mounting rail armament			None
Type of electric connection			Other
Rated current I_n		A	630
Min. busbar thickness		mm	5
Max. busbar thickness		mm	10
Width of the adapter		mm	185
Rail width		mm	30
Busbar distance		mm	60

Dimensions

