## **DATASHEET - M22-SWD-NOP**



Universal module, SmartWire-DT, front mount

M22-SWD-NOP Part no. Catalog No. 147637 Alternate Catalog

**EL-Nummer** (Norway)

M22-SWD-NOPQ

4560864



**Delivery program** 

Basic function accessories	SmartWire-DT universal slave
Fixing	Front fixing
Configuration	1 4 3 6 2 5
Connection to SmartWire-DT	yes

Design verification as per IEC/EN 61439				
Technical data for design verification				
Rated operational current for specified heat dissipation	In	Α	0	
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	0	
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	0	
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0.3	
Heat dissipation capacity	P <sub>diss</sub>	W	0	
Operating ambient temperature min.		°C	-30	
Operating ambient temperature max.		°C	55	
IEC/EN 61439 design verification				
10.2 Strength of materials and parts				
10.2.2 Corrosion resistance			Meets the product standard's requirements.	
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.	
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.	
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.	
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.	
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.	
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.	
10.2.7 Inscriptions			Meets the product standard's requirements.	
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.	
10.4 Clearances and creepage distances			Meets the product standard's requirements.	
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.	
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.	
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.	
10.8 Connections for external conductors			Is the panel builder's responsibility.	
10.9 Insulation properties				
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.	
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.	
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.	
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.	
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switch gear must be observed. $\label{eq:constraint}$	
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switch gear must be observed. $\label{eq:specification}$	

## **Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory Other

## **Approvals**

UL File No. UL Category Control No.	E29184 NKCR
CSA File No.	2324643
CSA Class No.	3211-07
North America Certification	Request filed for UL and CSA
Specially designed for North America	No

## **Additional product information (links)**

f1=1457&f2=1181&f3=1530;Download Wizard SWD-ASSIST http://applications.eaton.eu/sdlc?LX=11&amp