




Connection cable, 5p, DC current, coupling M12 flat, open end, L=10m



Powering Business Worldwide™

**Part no.** CSDS5A5CY2210  
**Catalog No.** 166987  
**Alternate Catalog No.** CSDS5A5CY2210

### Delivery program

Basic function			Accessories
Accessories			Connecting cables
Length		mm	10000
Pin assignment			
Voltage type			DC
Number of poles			5 pole
Style output side			Cable end, open
Style input side			Coupling, straight
<b>For use with</b>			
For use with			DC sensors, IntelliView E75-DST4..., 5 pole, M12

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

### Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])			
Number of poles			5
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			Other
Type of plug-in contact, box-sided			
Positioning cable feed, box-sided			Other
Cable length		m	10
Material of cable sheath			Other
Halogen free			No
Colour cable sheath			Black
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current In		A	0
Rated voltage		V	0
Continuity resistor		mOhm	0
Degree of protection (IP)			Other