



Fuse-link, high speed, 4000 A, AC 1000 V, 300 kA, 2 x size 4, 105 x 250 x 87 mm, aR, IEC, type K indicator



Part no. FUSE 4000A 1000V 24BKE/85 AR
Catalog No. 170M7530

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	4000
Rated voltage			AC 1000 V
Construction size			2 x size 4
Size			105 x 250 x 87 mm
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	300
usable for size/applications			Protection of power rectifiers
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	4000
Rated voltage		V	1000
Voltage type			AC
Rated switching capacity		kA	
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No