## Fixing rating plug 16A



## Part no. LPC16-ADAPTER 1713624

Product name Product name	Eaton LPC Accessory Adapter plate
Part no.	LPC16-ADAPTER
EAN	8711426532007
Product Length/Depth	95 millimetre
Product height	2 millimetre
Product width	76 millimetre
Product weight	1.6 gram
Compliances	CE
Product Tradename	LPC
Product Type	Accessory
Product Sub Type	Adapter plate
Globally Marketable	Yes
,	
Color	Gray
Туре	Adapter plate
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Rated operational current (le) - max	16 A
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	Not applicable.
10.11 Short-circuit rating	Not applicable.
10.12 Electromagnetic compatibility	Not applicable.
10.13 Mechanical function	Not applicable.

## Technical data ETIM 8.0 Circuit breakers and fuses (EG000020) / D-system screw adapter (EC000085) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Diazed screw adapter (ecl@ss10.0.1-27-14-21-13 [AKE285013]) Construction size DII Rated current A 16 Colour code Grey