

Analog I/O module, 2 analog inputs and 2 analog outputs, 0/4 to 20 mA

Part no. **XN-322-4AIO-I**
183182

Product name	Eaton XN-322 I/O module
Part no.	XN-322-4AIO-I
EAN	4015081781157
Product Length/Depth	104.2 millimetre
Product height	16.8 millimetre
Product width	80.3 millimetre
Product weight	0.055 kilogram
Certifications	IEC/EN 61000-6-4 UL File No.: E135462 IEC/EN 61000-6-2 CE CULus IEC/EN 61131-2
Product Tradename	XN-322
Product Type	I/O module
Product Sub Type	None
Catalog Notes	The max. heat dissipation is specified as the maximum power produced inside the device's housing.
Current measurement	50 Ω typ., input resistance 0 - 20 mA
Electric connection type	Plug-in connection
Features	Input, current Analog outputs configurable Output, current Analog inputs configurable Fieldbus connection over separate bus coupler possible Input signal, configurable
Fitted with:	1 kHz, third-order low-pass input filter Parameterizable Software input filter
Value representation	SIGNED16, Current measurement
Current consumption	55 mA (typ.), for +5 V power supply (internal), Power supply - Input None mA (typ.), for +24 V, Power supply - Input
Degree of protection	IP20 NEMA 1
Limit frequency	1 kHz (third-order low-pass filter)
Mounting method	Rail mounting possible
Number of channels	2, Analog Inputs
Overvoltage category	III
Pollution degree	3
Product category	XN-322 analog input and output module
Resolution	12 Bit (Analog outputs) 16 Bit (Analog inputs)
Type	Analog mixed module with 2 analog outputs 0/4 to 20 mA (12 bit) and 2 analog inputs 0/4 to 20 mA (16 bit). XN300 I/O slice module
Used with	XN300 XN-312-...
Voltage type	DC
Height of fall (IEC/EN 60068-2-32) - max	1 m
Mounting position	Horizontal
Shock resistance	15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
Vibration resistance	5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g

Air pressure		795 - 1080 hPa (operation)
Ambient operating temperature - min		0 °C
Ambient operating temperature - max		60 °C
Ambient storage temperature - min		-20 °C
Ambient storage temperature - max		85 °C
Climatic proofing		Dry heat to IEC 60068-2-2 Damp heat, constant, to IEC 60068-2-3
Environmental conditions		Condensation: prevent with appropriate measures
Relative humidity		0 - 95 % (non-condensing)
Air discharge		8 kV
Burst impulse		2 kV, Supply cable 1 kV, Signal cable
Contact discharge		4 kV
Electromagnetic fields		1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
Emitted interference		40 dB (at 30 - 230 MHz, Class A, radiated, high frequency) 47 dB (at 230 - 1000 MHz, Class A, radiated, high frequency)
Radiated RFI		10 V
Surge rating		0.5/0.5 kV, Supply cable, balanced/unbalanced), EMC 1 kV, Signal cable, unbalanced, EMC
Voltage dips		Voltage dips: 10 ms/Voltage fluctuations: Yes
Terminal capacity		0.25 - 1.5 mm ² , with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.2 - 1.5 mm ² , solid, H07V-U 24 - 16 AWG 0.25 - 1.5 mm ² , with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.2 - 1.5 mm ² , flexible without ferrule, H07V-K
Gauge pin		A1 (according to IEC/EN 60947-1)
Stripping length (main cable)		10 mm
Insulating material group		I
Rated operational current (I _e)		0.051 A (supply input)
Rated operational voltage		160 V (terminations) 24 V (X5)
Short-circuit protection		Yes, Short-circuit strength, Analog outputs
Supply voltage at AC, 50 Hz - min		0
Supply voltage at AC, 50 Hz - max		0
Supply voltage at DC - min		18
Supply voltage at DC - max		30
Connection type		Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction 2 conductors, Analog outputs, Output current 2 conductors, Current measurement
Protocol		Other bus systems
Accuracy		± 0.5 % of full scale, Analog outputs ± 0.5 % of full scale, Current measurement
Input		2 Analog inputs (0/4 - 20 mA)
Input current		Max. 100 mA
Load current		Not specified by plug manufacturer
Measured variables		Current
Number of inputs (analog)		2
Number of outputs (analog)		2
Output		2 Analog Outputs (0/4 - 20 mA)
Output current		0 - 20 mA, Analog outputs
Refresh time		1 ms (analog inputs, all channels)
Resistive load		≤ 500 Ω, analog outputs

Value refresh time/cycle time		Min. 1 / 1 ms (per channel / all channels), Analog Inputs
Explosion safety category for dust		None
Explosion safety category for gas		None
Potential isolation		Analog inputs: no Power supply, Input: no
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0.851 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		1.85 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Fieldbus, decentr. periphery - analogue I/O module (EC001596)		
Electric engineering, automation, process control engineering / Control / Field bus, decentralized peripheral / Field bus, decentralized peripheral - analogue I/O module (ecI@ss10.0.1-27-24-26-01 [BAA061014])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	18 - 30
Voltage type of supply voltage		DC
Input, current		Yes
Input, voltage		No
Input, resistor		No
Input, resistance thermometer		No
Input, thermocouple		No
Input signal, configurable		Yes
Resolution of the analogue inputs	Bit	16
Output, current		Yes
Output, voltage		No
Output signal configurable		No
Resolution of the analogue outputs	Bit	12
Number of analogue inputs		2
Number of analogue outputs		2

Analogue inputs configurable		Yes
Analogue outputs configurable		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces USB		0
Number of HW-interfaces other		1
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		Yes
Radio standard Bluetooth		No
Radio standard Wi-Fi 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
System accessory		Yes
Degree of protection (IP)		IP20
Degree of protection (NEMA)		1
Type of electric connection		Plug-in connection
Fieldbus connection over separate bus coupler possible		Yes
Rail mounting possible		Yes
Wall mounting/direct mounting		No
Front built-in possible		No
Rack-assembly possible		No
Suitable for safety functions		No
SIL according to IEC 61508		None
Performance level according to EN ISO 13849-1		None
Appendant operation agent (Ex ia)		No
Appendant operation agent (Ex ib)		No
Explosion safety category for gas		None

Explosion safety category for dust		None
Width	mm	80.3
Height	mm	16.8
Depth	mm	104.2