## DATASHEET - XMW0606CDC-C



XW\_front plate closed PKZ\_IP55\_H150

Part no. Catalog No. XMW0606CDC-C 194451



## Design verification as per IEC/EN 61439

| IEC/EN 61439 design verification   |  |
|--|--|
| 10.2 Strength of materials and parts   |  |
| 10.2.2 Corrosion resistance  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures   | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   | Meets the product standard's requirements.   |
| 10.2.5 Lifting   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   | Is the panel builder's responsibility.   |
| 10.5 Protection against electric shock   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |  |
| 10.9.2 Power-frequency electric strength   | U <sub>i</sub> = 800 V AC  |
| 10.9.3 Impulse withstand voltage   | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## **Technical data ETIM 7.0**

Cabinet enclosures (EG000011) / Front plate (switchgear cabinet) (EC000456)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Elements for switching cabinet, housing, rack / Front plate (electrical cabinet) (ecl@ss10.0.1-27-18-28-06 [AKE465013]) Width 565 mm Height 148.5 mm 600 Suitable for enclosure building width mm 150 Suitable for enclosure building height mm Number of height units 0 Material Steel Surface finishing Powder coating