DATASHEET - M22-I1-*



Surface mounting enclosure, 1 mounting location, M22

Powering Business Worldwide*

Part no. M22-I1-* Catalog No. 197631

Delivery program		
Basic function accessories		Surface mounting enclosure
Housing		Insulated material
		With high-grade steel screws Individually markable with pushbutton configurator
Number of locations	Qty.	1
Cable entry knockouts		
Cable entry		rear: 2 x M16 at top: 1 x M20 lateral: 2 x M20/M25 (1 x each side)
Colour		
RAL Value		RAL 7035
Colour		Enclosure base anthracite
Connection to SmartWire-DT		no
For use with		1 x ∅ 22.5
For use with		(Illuminated) pushbuttons (Illuminated) selector switches Key-operated pushbuttons Indicator light

Technical data ETIM 7.0

Technical uata ETIW 7.0				
Low-voltage industrial components (EG000017) / Enclosure for control circuit devices	es (EC000200)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss10.0.1-27-37-12-05 [AKF023014])				
Number of command positions		1		
Construction type housing		Surface mounting housing		
Material housing		Plastic		
Material quality housing		Other		
Diameter openings	mm	22.5		
Colour housing cover		Grey		
Degree of protection (IP)		IP67/IP69K		
Degree of protection (NEMA)		4X		
Width	mm	72		
Height	mm	80		
Depth	mm	56		

controlled stop/emergency-stop buttons with yellow label

Dimensions

