

On-Off switch, 6 pole + 1 N/O + 1 N/C, 32 A, 90 °, surface mounting

Part no. **T3-4-15164/I2**
222899

| | |
|--|---|
| Product name | Eaton Moeller® series T3 On-Off switch |
| Part no. | T3-4-15164/I2 |
| EAN | 4015082228996 |
| Product Length/Depth | 181 millimetre |
| Product height | 127 millimetre |
| Product width | 100 millimetre |
| Product weight | 0.594 kilogram |
| Compliances | CE Marked |
| Certifications | UL 508 EN 60947-3 IEC 60947 CSA Std. C22.2 No. 14-05 VDE CSA Class No.: 3211-07 UL 60947-4-1 UL CSA-C22.2 No. 60947-4-1-14 UL File No.: E36332 IEC/EN 60204 UL Category Control No.: NLRV IEC/EN 60947 CSA CE CSA-C22.2 No. 94 CSA File No.: 012528 VDE 0660 IEC/EN 60947-3 |
| Product Tradename | T3 |
| Product Type | On-Off switch |
| Product Sub Type | None |
| Catalog Notes | Rated Short-time Withstand Current (Icw) for a time of 1 second |
| Fitted with: | Black thumb grip and front plate |
| Inscription | 0-1 |
| Number of poles | 6 |
| Degree of protection | NEMA 12 |
| Degree of protection (front side) | IP65 |
| Lifespan, mechanical | 500,000 Operations |
| Mounting method | Surface mounting |
| Mounting position | As required |
| Number of contact units | 4 |
| Operating frequency | 1200 Operations/h |
| Overvoltage category | III |
| Pollution degree | 3 |
| Rated impulse withstand voltage (Uimp) | 6000 V AC |
| Safe isolation | 440 V AC, Between the contacts, According to EN 61140 |
| Safety parameter (EN ISO 13849-1) | B10d values as per EN ISO 13849-1, table C.1 |
| Shock resistance | 12 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| Suitable for | Ground mounting Branch circuits, suitable as motor disconnect, (UL/CSA) |
| Switching angle | 90 ° |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 40 °C |
| Ambient operating temperature (enclosed) - min | -25 °C |

| | | |
|--|--|---|
| Ambient operating temperature (enclosed) - max | | 40 °C |
| Climatic proofing | | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| Terminal capacity | | 2 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 14 - 10 AWG, solid or flexible with ferrule 1 x (0.75 - 4) mm ² , flexible with ferrules to DIN 46228 1 x (1 - 6) mm ² , solid or stranded 2 x (1 - 6) mm ² , solid or stranded |
| Screw size | | M4, Terminal screw |
| Tightening torque | | 17.7 lb-in, Screw terminals 1.6 Nm, Screw terminals |
| Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3) | | 260 A |
| Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) | | 260 A |
| Rated breaking capacity at 500 V (cos phi to IEC 60947-3) | | 240 A |
| Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3) | | 170 A |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | | 23.7 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | | 23.7 A |
| Rated operational current (Ie) at AC-3, 500 V | | 23.7 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | | 14.7 A |
| Rated operational current (Ie) at AC-21, 440 V | | 32 A |
| Rated operational current (Ie) at AC-23A, 230 V | | 32 A |
| Rated operational current (Ie) at AC-23A, 400 V, 415 V | | 32 A |
| Rated operational current (Ie) at AC-23A, 500 V | | 26.4 A |
| Rated operational current (Ie) at AC-23A, 690 V | | 17 A |
| Rated operational current (Ie) at DC-1, load-break switches I/r = 1 ms | | 25 A |
| Rated operational current (Ie) at DC-13, control switches L/R = 50 ms | | 20 A |
| Rated operational current (Ie) at DC-21, 240 V | | 1 A |
| Rated operational current (Ie) at DC-23A, 24 V | | 25 A |
| Rated operational current (Ie) at DC-23A, 48 V | | 25 A |
| Rated operational current (Ie) at DC-23A, 60 V | | 25 A |
| Rated operational current (Ie) at DC-23A, 120 V | | 12 A |
| Rated operational current (Ie) at DC-23A, 240 V | | 5 A |
| Rated operational current (Ie) star-delta at AC-3, 220/230 V | | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 380/400 V | | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 500 V | | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 690 V | | 25.5 A |
| Rated operational power at AC-3, 380/400 V, 50 Hz | | 11 kW |
| Rated operational power at AC-3, 415 V, 50 Hz | | 11 kW |
| Rated operational power at AC-3, 500 V, 50 Hz | | 15 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | | 11 kW |
| Rated operational power at AC-23A, 220/230 V, 50 Hz | | 7.5 kW |
| Rated operational power at AC-23A, 400 V, 50 Hz | | 15 kW |
| Rated operational power at AC-23A, 500 V, 50 Hz | | 15 kW |
| Rated operational power at AC-23A, 690 V, 50 Hz | | 15 kW |
| Rated operational power star-delta at 220/230 V, 50 Hz | | 7.5 kW |
| Rated operational power star-delta at 380/400 V, 50 Hz | | 15 kW |
| Rated operational power star-delta at 500 V, 50 Hz | | 18.5 kW |
| Rated operational power star-delta at 690 V, 50 Hz | | 22 kW |
| Rated operational voltage (Ue) at AC - min | | 690 V |
| Rated operational voltage (Ue) at AC - max | | 690 V |
| Rated uninterrupted current (Iu) | | 32 A |
| Uninterrupted current | | Rated uninterrupted current Iu is specified for max. cross-section. |
| Rated conditional short-circuit current (Iq) | | 1 kA |
| Rated short-time withstand current (Icw) | | 0.65 kA 650 A, Contacts, 1 second |

| | | |
|--|--|---|
| Short-circuit current rating (basic rating) | | 40A, max. Fuse, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) |
| Short-circuit current rating (high fault) | | 40 A, Class J, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA) |
| Short-circuit protection rating | | 35 A gG/gL, Fuse, Contacts |
| Load rating | | 1.3 x I# (with intermittent operation class 12, 60 % duty factor) 1.6 x I# (with intermittent operation class 12, 40 % duty factor) 2 x I# (with intermittent operation class 12, 25 % duty factor) |
| Number of contacts in series at DC-21A, 240 V | | 1 |
| Number of contacts in series at DC-23A, 24 V | | 1 |
| Number of contacts in series at DC-23A, 48 V | | 2 |
| Number of contacts in series at DC-23A, 60 V | | 3 |
| Number of contacts in series at DC-23A, 120 V | | 3 |
| Number of contacts in series at DC-23A, 240 V | | 5 |
| Switching capacity (main contacts, general use) | | 25 A, Rated uninterrupted current max. (UL/CSA) |
| Switching capacity (auxiliary contacts, general use) | | 10A, IU, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | | A600 (UL/CSA) P600 (UL/CSA) |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3) | | 320 A |
| Voltage per contact pair in series | | 60 V |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase | | 1.5 HP |
| Assigned motor power at 200/208 V, 60 Hz, 1-phase | | 3 HP |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase | | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase | | 3 HP |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase | | 7.5 HP |
| Assigned motor power at 575/600 V, 60 Hz, 3-phase | | 10 HP |
| Control circuit reliability | | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| Number of auxiliary contacts (change-over contacts) | | 0 |
| Number of auxiliary contacts (normally closed contacts) | | 1 |
| Number of auxiliary contacts (normally open contacts) | | 1 |
| Actuator color | | Black |
| Actuator function | | Maintained |
| Actuator type | | Short thumb-grip |
| Equipment heat dissipation, current-dependent P _{vid} | | 1.1 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 1.1 W |
| Rated operational current for specified heat dissipation (I _n) | | 32 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | UV resistance only in connection with protective shield. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |

| | | |
|--|--|--|
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

| | | |
|---|----|----------------------------|
| Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ec!@ss10.0.1-27-37-14-03 [AKF060013]) | | |
| Version as main switch | | No |
| Version as maintenance-/service switch | | No |
| Version as safety switch | | No |
| Version as emergency stop installation | | No |
| Version as reversing switch | | No |
| Number of switches | | 1 |
| Max. rated operation voltage U _e AC | V | 690 |
| Rated operating voltage | V | 690 - 690 |
| Rated permanent current I _u | A | 32 |
| Rated permanent current at AC-23, 400 V | A | 32 |
| Rated permanent current at AC-21, 400 V | A | 32 |
| Rated operation power at AC-3, 400 V | kW | 11 |
| Rated short-time withstand current I _{cw} | kA | 0.65 |
| Rated operation power at AC-23, 400 V | kW | 15 |
| Switching power at 400 V | kW | 15 |
| Conditioned rated short-circuit current I _q | kA | 1 |
| Number of poles | | 6 |
| Number of auxiliary contacts as normally closed contact | | 1 |
| Number of auxiliary contacts as normally open contact | | 1 |
| Number of auxiliary contacts as change-over contact | | 0 |
| Motor drive optional | | No |
| Motor drive integrated | | No |
| Voltage release optional | | No |
| Device construction | | Complete device in housing |
| Suitable for floor mounting | | Yes |
| Suitable for front mounting 4-hole | | No |
| Suitable for front mounting centre | | No |
| Suitable for distribution board installation | | No |
| Suitable for intermediate mounting | | No |
| Colour control element | | Black |
| Type of control element | | Short thumb-grip |
| Interlockable | | No |
| Type of electrical connection of main circuit | | Screw connection |
| Degree of protection (IP), front side | | IP65 |
| Degree of protection (NEMA) | | 12 |