

## Auxiliary contact, for FI..., 1N/O+1N/C, 0.5HP

**Part no.**                    **FIP-XHI11**  
**225121**

Product name	Eaton Distribution parts
Part no.	FIP-XHI11
EAN	4015082251215
Product Length/Depth	80 millimetre
Product height	65.5 millimetre
Product width	8.8 millimetre
Product weight	0.04 kilogram
Compliances	RoHS conform
Certifications	EN45545-2 IEC 61373
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
PDH Status	Active
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Accessory/spare part type	Auxiliary contacts
Additional equipment required	Auxiliary switch
Admissible back-up fuse - max	6 A gL
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Assembly width	0.5
Contact function	1 M + 1 B
Degree of protection	IP40
Device fitting	Universal
Enclosure width	90 mm
Frame	Standard front dimension: 45 mm
Frequency rating	50 Hz / 60 Hz
Lifespan, mechanical	6000 operations
Mounting method	Top-hat rail IEC/EN 60715
Mounting width	8.8 mm (0.5 space units)
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	2
Number of switches (fault signal)	0
Rated insulation voltage (Ui)	440
Rated operational current	6 A (250 V AC-13) 6 A (230 V AC-11) 0.5 A (230 V DC-13) 4 A (60 V DC-13) 2 A (400 V AC-13) 2 A (110 V DC-13)
Rated operational voltage (Ue) - max	230 V
Rated switch current	3 A
Rated switch current [7EF006706]	A
Rated voltage [7EF00228]	V
Special features	IP20 (switch)

Suitable for current of main contact unit - max		0 A
Suitable for max. current main contact unit [7EF008730]		A
Terminal capacity (cable)		0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x) 0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (2x)
Terminal capacity (solid wire)		0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x) 0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (2x)
Terminal protection		Protection against electric shock to IEC 536
Terminal type		Twin-purpose terminals
Type		Accessory Accessory for residual current circuit breaker
Used with		Accessory Accessory for residual current circuit breaker
Voltage rating (V/mA) - min		24
Voltage type		AC

## Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Universal
Additional equipment		Auxiliary switch
Installed at the factory		No
Width in number of modular spacings		0.5
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	3
Rated voltage	V	230
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	0