DATASHEET - ZP-ASA/24



Shunt release, 12-110V, 1HP

Part no. ZP-ASA/24 Catalog No. 248438

EL-Nummer (Norway)

1609470



Delivery program

Basic function	Accessories for miniature circuit-breaker Accessories for combined residual-current/power circuit-breakers
Basic function accessories	Shunt release
Application	Switchgear for industrial and advanced commercial applications
Product range	Accessory
Side mounting	for fitting on left to: FAZ, FRBmM-1N, Z-MS
Contact sequence	01

Technical data

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-5
Operating ambient temperature max.	°C	40

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])

j		
Device fitting		Other
Additional equipment		Shunt release (for power circuit breaker)
Attached at delivery		No
Assembly width (TE)		1
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	А	0
Rated voltage	V	24
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	А	15

Dimensions

