



Connecting cable for networking devices via easyNet, 2xRJ45, 150cm

**Part no.** EASY-NT-150  
**Catalog No.** 256285

**EL-Nummer (Norway)** 4520998

### Delivery program

Description			Connection cable for XC200 to interface switch
Length		m	1.5
For use with			easy800 MFD-...-CP8...
For use with			easyNet

### Technical data

Pairs 2 x 0.14 mm<sup>2</sup>

Conductor material			E-Cu 58 F21 nach DIN 40500 Teil 4
Conductor material			Max. 0.49 mm (Cu wire bare 7 x 0.16 mm <sup>2</sup> )
Core			0.60 mm ±0.10 (dielectric polyethylene, halogen free, every two cores paired and twisted: wsbl-bl, wsor-or, wsgn-gn, wsbr-br)
Stranding			Four pairs
Sheath		mm <sup>2</sup>	4.5 mm ± 0.2 (halogen free casing material, flame retardant (FRNC))

### Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	0
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	0
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	0
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			
10.2.3.1 Verification of thermal stability of enclosures			
10.2.3.2 Verification of resistance of insulating materials to normal heat			
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			
10.2.4 Resistance to ultra-violet (UV) radiation			
10.2.5 Lifting			
10.2.6 Mechanical impact			
10.2.7 Inscriptions			
10.3 Degree of protection of ASSEMBLIES			
10.4 Clearances and creepage distances			
10.5 Protection against electric shock			
10.6 Incorporation of switching devices and components			
10.7 Internal electrical circuits and connections			
10.8 Connections for external conductors			
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			
10.9.3 Impulse withstand voltage			
10.9.4 Testing of enclosures made of insulating material			
10.10 Temperature rise			

10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Cables (EG000001) / Data and communication cable (copper) (EC003249)		
Conductor surface		Bare
Diameter conductor	mm	4.5
Nominal cross section conductor	mm <sup>2</sup>	0.14
AWG-size		26
Conductor category		Class 2 = stranded
Number of cores		8
Number of stranding elements		2
Stranding element		Pairs
Core insulation material		Other
Specification core insulation		
Core identification		Colour
Screen over stranding element		None
Stranding		
Screen over stranding		None
Longitudinal water blocking cable		
Radial water blocking cable		
Protective sheath		
Armouring		
Material outer sheath		
Specification material outer sheath		
Colour outer sheath		Grey
Reaction-to-fire class according to EN 13501-6		
Smoke development class according to EN 13501-6		
Euro class flaming droplets/particles according to EN 13501-6		
Euro class acidity according to EN 13501-6		
Halogen free (acc. EN 60754-1/2)		Yes
Halogen free (acc. IEC 60754-2)		
Flame retardant		No
Low smoke (acc. EN 61034-2)		No
Low smoke (acc. IEC 61034-2)		Yes
Oil resistant (acc. EN 60811-404)		
Oil resistant (acc. IEC 60811-404)		
Insulation integrity in accordance with IEC 60331		
Circuit integrity		
Outer diameter approx.	mm	4.5
Min. permitted bending radius, moving application with forced guidance	mm	
Min. permitted bending radius, moving application/free movement	mm	
Min. permitted bending radius, stationary application/permanent installation	mm	
Permitted cable outer temperature during assembling/handling	°C	-25 - 60
Permitted cable outer temperature after assembling without vibration	°C	-25 - 60
Category		5E
NVP value	%	67
Underground installation		No
UV resistant		

## Approvals

Product Standards		IEC/EN see Technical Data; UL 508; CSA C22.2 No. 142-M1987; CSA C22.2 No. 213-M1987; CE marking
UL File No.		E135462

UL Category Control No.			NRAQ
CSA File No.			012528
CSA Class No.			2258-02
North America Certification			UL listed, CSA certified
Degree of Protection			IEC: IP20, UL/CSA Type: -