



Fuse-link, LV, 25 A, AC 660 V, DC 250 V, BS88/A2, 22 x 82 mm, gL/gG, BS

25H07-660

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	25H07-660
EAN	5027590470186
Product Length/Depth	84.5 millimetre
Product height	21 millimetre
Product width	21 millimetre
Product weight	48.75 gram
Compliances	Contact Manufacturer
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	25 A
Voltage rating	690 V
Voltage type	AC/DC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	H07-660
Fuse size	BS88/A2
Fitted with:	Offset bolted tags
Connection	Bolt-on

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A2
Type of current		AC/DC
Rated voltage AC	V	690
Rated voltage DC	V	460
Rated current	A	25
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	3.1
Mounting holes		M5
Centre-to-centre distance of connections	mm	71.5