DATASHEET - Z-PUL230/SS

Pushbutton with LED, 230AC/DC, 2N/O, 16A, orange, 1HP



Part no. Catalog No. Z-PUL230/SS 276297



Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|------------------|---|----|
| Rated operational current for specified heat dissipation | I _n | А | 16 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 2 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 4 |

Technical data ETIM 7.0

| Devices for distribution board-/surface mounting (EG000062) / Push button for di | stribution board (E | EC001546) | |
|---|---------------------|------------|---|
| Electric engineering, automation, process control engineering / Electrical install (ecl@ss10.0.1-27-14-23-02 [AFZ814014]) | ation, device / Mo | ıdular ser | al built-in device for electrical circuit distributors / Push button for distribution board |
| Number of contacts as normally closed contact | | | 0 |
| Number of contacts as normally open contact | | | 2 |
| Number of contacts as change-over contact | | | 0 |
| Switching current | | А | 16 |
| Switching voltage | | V | 250 |
| Voltage type | | | AC |
| With signal lamp | | | Yes |
| Colour calotte | | | Not applicable |
| Lamp type | | | LED |
| Lamp socket | | | Other |
| Max. lamp power | | W | 2 |
| Lamp voltage | | V | 110 - 240 |
| Colour button | | | Green |
| Width in number of modular spacings | | | 1 |
| Built-in depth | | mm | 60 |
| Degree of protection (IP) | | | IP40 |