DATASHEET - FAZ-D25/1N



Miniature circuit breaker (MCB), 25 A, 1p+N, characteristic: D

Powering Business Worldwide*

Part no. FAZ-D25/1N Catalog No. 278699 Alternate Catalog FAZ-D25/1N

No.

EL-Nummer 1666782 (Norway)

Similar to illustration

Delivery program			
Basic function			Miniature circuit-breakers
Number of poles			1 pole+N
Tripping characteristic			D
Application			Switchgear for industrial and advanced commercial applications
Rated current	In	Α	25
Rated switching capacity acc. to IEC/EN 60947-2	I _{cu}	kA	15
Product range			FAZ

Technical data Electrical

Rated switching capacity acc. to IEC/EN 60947-2	I _{cu}	kA 15	
---	-----------------	-------	--

Design verification as per IEC/EN 61439

Design vernication as per 1EG/EN 01433			
Technical data for design verification			
Rated operational current for specified heat dissipation	In	Α	25
Heat dissipation per pole, current-dependent	P _{vid}	W	0
Equipment heat dissipation, current-dependent	P _{vid}	W	2.9
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P _{diss}	W	0
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	75
			linear, per +1 °C, results in a 0.5% reduction of current carrying capacity
EC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects $$			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.

10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042) Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014]) Release characteristic D 2 Number of poles (total) Number of protected poles Rated current Α 25 Rated voltage 230 440 Rated insulation voltage Ui Rated impulse withstand voltage Uimp kV 4 Rated short-circuit breaking capacity Icn EN 60898 at 230 V kΑ 10 Rated short-circuit breaking capacity Icn EN 60898 at 400 V kΑ 10 kΑ Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 ${
m V}$ 15 Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V kA 15 Voltage type AC Hz 50 - 60 Frequency **Current limiting class** 3 Suitable for flush-mounted installation No Concurrently switching N-neutral Yes Over voltage category 3

2

2

70.5

IP20

-25 - 75

1 - 25

1 - 25

Yes

Additional product information (links)

emperature dependency, derating	https://www.eaton.com/content/dam/eaton/technicaldocumentation/technical-data-tables/Derating table FAZ.pdf

°C

mm²

mm²

Pollution degree

Built-in depth

Additional equipment possible

Degree of protection (IP)

Width in number of modular spacings

Ambient temperature during operating

Connectable conductor cross section multi-wired

Connectable conductor cross section solid-core