

**Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40...-
ASA...IHK...WHK, Z-MS, 1N/O+1N/C, 0.5HP**

Part no. ZP-IHK
286052
EL Number 1609488
(Norway)

Product name	Eaton Distribution parts
Part no.	ZP-IHK
EAN	4015082860523
Product Length/Depth	80 millimetre
Product height	75 millimetre
Product width	8.8 millimetre
Product weight	0.043 kilogram
Compliances	RoHS conform
Certifications	IEC 61373 EN45545-2
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Accessory/spare part type	Auxiliary contacts
Additional equipment required	Auxiliary switch
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for industrial and advanced commercial applications
Assembly width	0.5
Device fitting	Universal
EL number	1609488
Mounting method	For fitting on left to: LS, FI/LS
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	2
Number of switches (fault signal)	0
Rated operational voltage (Ue) - max	230 V
Rated switch current	3 A
Rated switch current [7EF006706]	A
Rated voltage [7EF000228]	V
Suitable for current of main contact unit - max	6 A
Suitable for max. current main contact unit [7EF008730]	A
Type	Accessory Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker
Used with	Auxiliary contacts Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker Accessory
Voltage type	AC

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Device fitting			Universal
Additional equipment			Auxiliary switch
Installed at the factory			No
Width in number of modular spacings			0.5
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	3
Rated voltage		V	230
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			2
Suitable for max. current main contact unit		A	6