



**Transparent door**

**Part no.** BP-DT-400/10  
**Catalog No.** 286730

**EL-Nummer (Norway)** 0002456063

**Delivery program**

|                      |  |    |                       |
|----------------------|--|----|-----------------------|
| Mounting type        |  |    | Surface mounted       |
| Material             |  |    | Sheet steel/plastic   |
| Door interlock       |  |    | Three-point turn-lock |
| Degree of Protection |  |    | IP30                  |
| Surface finish       |  |    | With powder coating   |
| Width                |  | mm | 400                   |
| Height               |  | mm | 1060                  |
| Suitable for height  |  | mm | 1060                  |
| Suitable for width   |  | mm | 400                   |
| Colour               |  |    | light gray (RAL 7035) |
| Door/Flap            |  |    | Transparent           |

**Technical data ETIM 7.0**

|   |  |    |                |
|---|--|----|----------------|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)  |  |    |                |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ec1@ss10.0.1-27-18-22-04 [ACN614011]) |  |    |                |
| Model   |  |    | Stop door      |
| Version as glazed door  |  |    | Yes            |
| Version as door for disconnecting switch interlocking   |  |    | No             |
| Width   |  | mm | 397            |
| Height  |  | mm | 996.5          |
| Depth   |  | mm | 35             |
| EMC-version   |  |    | No             |
| Material  |  |    | Steel          |
| Surface finishing   |  |    | Powder coating |
| Colour  |  |    | Grey           |
| Degree of protection (IP)   |  |    | IP30           |
| Degree of protection (NEMA)   |  |    |                |