



Fuse-link, low voltage, 315 A, AC 660 V, BS88, 49 x 110 mm, gL/gG, BS

315N20

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		315N20
EAN		5027590043618
Product Length/Depth		52 millimetre
Product height		52 millimetre
Product width		112 millimetre
Product weight		505 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC 60269 EAC BS88
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		315 A
Voltage rating		660 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Fuse type		N20
Connection		92.5 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC
Rated voltage AC	V	660
Rated voltage DC	V	
Rated current	A	315
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	25
Mounting holes		M10
Centre-to-centre distance of connections	mm	92.5