



Fuse-link, low voltage, 315 A, AC 690 V, 120 kA, NH3, aM, IEC, dual indicator, live gripping lugs



**Part no.** NH FUSE315A 690V aM SIZE 3  
**Catalog No.** 315NHM3B-690

**EL-Nummer (Norway)** 0001664159

Similar to illustration

### Delivery program

|                              |   |    |  |
|------------------------------|---|----|--|
| Product range                |   |    | Fuse   |
| Basic function               |   |    | Fuse-link  |
| Field of application         |   |    | low voltage  |
| Rated current                | I | A  | 315  |
| Rated voltage                |   |    | AC 690 V   |
| Construction size            |   |    | NH3  |
| Utilization category         |   |    | aM   |
| Status indicator             |   |    | dual indicator                                       |
| Description                  |   |    | live gripping lugs                                   |
| Breaking Capacity            |   | kA | 120  |
| usable for size/applications |   |    | industrial   |
| Standard/Approval            |   |    | IEC  |
| Shape                        |   |    | square body with knife blade contacts                |
| Standards/Regulations        |   |    | IEC 60269-2 fuse system A<br>DIN 43620<br>VDE 0636-2 |

### Technical data ETIM 7.0

|   |  |    |                                   |
|---|--|----|-----------------------------------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |                                   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |                                   |
| Construction size   |  |    | NH3                               |
| Rated current   |  | A  | 315                               |
| Rated voltage   |  | V  | 690                               |
| Voltage type  |  |    | AC                                |
| Rated switching capacity  |  | kA | 120                               |
| Utilization category  |  |    | aM (switchgear protection)        |
| Type of fuse status indicator   |  |    | Combination fuse status indicator |
| Insulated metal gripping lugs (IMGL)  |  |    | No                                |