



Fuse-link, low voltage, 355 A, AC 415 V, 80 kA, BS88/J, 38 x 131 mm, gL/gG, BS, 92 mm fixing centres



Part no. 355AMP 415V AC TYPE J
Catalog No. 355PJ31-7

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|----------------------------|
| Product range | | | Fuse |
| Basic function | | | Utility fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 355 |
| Rated voltage | | | AC 415 V |
| Construction size | | | BS88/J |
| Size | | | 38 x 131 mm |
| Utilization category | | | gL/gG |
| Description | | | 92 mm fixing centres |
| Breaking Capacity | | kA | 80 |
| usable for size/applications | | | feeder pillars |
| Standard/Approval | | | BS |
| Shape | | | dual bolted tags (slotted) |
| Standards/Regulations | | | BS88-2 IEC 60269-2 |
| Optional accessories | | | fuse-holder JW4 |

Technical data ETIM 7.0

| | | | |
|---|--|----|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 355 |
| Rated voltage | | V | 415 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 80 |
| Utilization category | | | Other |
| Type of fuse status indicator | | | None |
| Insulated metal gripping lugs (IMGL) | | | No |