CGL+ CGVISION TOUCHSCREEN G/CONTROLLER



Catalog No. 40071361084

Delivery program

Mounting Nominal Voltage 230 ETIM Class EC002005 Permissible Ambient Temperature - Max Permissible Ambient Temperature - Min Permissible Ambient Temperature - Min Port Suitable Ext 10 lash Book Mounting Suitable Ext 10 lash Book Mounting	errer, bregram		
Nominal Voltage ETIM Class Permissible Ambient Temperature - Max Permissible Ambient Temperature - Min Permissible Ambient Temperature - Min Permissible Ambient Temperature - Min Portuge of the state of the			
ETIM Class Permissible Ambient Temperature - Max Permissible Ambient Temperature - Min C 35 Permissible Ambient Temperature - Min Frequency 50/60 Hz	Mounting		Wall surface mounting
Permissible Ambient Temperature - Max °C 35 Permissible Ambient Temperature - Min °C 0 Frequency 50/60 Hz	Nominal Voltage		230
Permissible Ambient Temperature - Min C O Frequency 50/60 Hz	ETIM Class		EC002005
Permissible Ambient Temperature - Min C O Frequency 50/60 Hz			
Frequency 50/60 Hz	Permissible Ambient Temperature - Max	°C	35
	Permissible Ambient Temperature - Min	°C	0
Suitable For 10 lash Pook Mounting	Frequency		50/60 Hz
Suitable For 10 Inab Pools Mounting			
Suitable For 15 mich nack woulding False	Suitable For 19 Inch Rack Mounting		False
Color Housing White	Color Housing		White
Testing System CGLine +	Testing System		CGLine +

Technical data ETIM 7.0

Suitable for 19 inch rack mounting

recliffical data ETHI 7.0			
Accessories for lighting (EG000030) / Test device for emergency power luminaires (EC002005)			
Electric engineering, automation, process control engineering / Lighting installation, device / Components for lighting installation / Test device for emergency power luminaires (ecl@ss10.0.1-27-11-11-31 [ADI261007])			
Length	mm		
Width	mm		
Height	mm		