



Fuse-link, low voltage, 40 A, AC 400 V, 120 kA, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs

Part no. **NH FUSE 40A 400V GG/GL SIZE 000**  
 Catalog No. **40NHG000BI-400**

Similar to illustration

### Delivery program

|                              |   |    |  |
|------------------------------|---|----|--|
| Product range                |   |    | Fuse   |
| Basic function               |   |    | Fuse-link  |
| Field of application         |   |    | low voltage  |
| Rated current                | I | A  | 40   |
| Rated voltage                |   |    | AC 400 V   |
| Construction size            |   |    | NH000  |
| Utilization category         |   |    | gL/gG  |
| Status indicator             |   |    | dual indicator                                       |
| Description                  |   |    | insulated gripping lugs                              |
| Breaking Capacity            |   | kA | 120  |
| usable for size/applications |   |    | industrial   |
| Standard/Approval            |   |    | IEC  |
| Shape                        |   |    | square body with knife blade contacts                |
| Standards/Regulations        |   |    | IEC 60269-2 fuse system A<br>DIN 43620<br>VDE 0636-2 |

### Technical data ETIM 7.0

|   |  |    |   |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |   |
| Construction size   |  |    | NH000   |
| Rated current   |  | A  | 40  |
| Rated voltage   |  | V  | 400   |
| Voltage type  |  |    | AC  |
| Rated switching capacity  |  | kA | 120   |
| Utilization category  |  |    | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator   |  |    | Combination fuse status indicator             |
| Insulated metal gripping lugs (IMGL)  |  |    | Yes   |

### Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (PDF) | <a href="http://www1.cooperbusssmann.com/pdf/1d43a21b-d2a9-476a-8090-9972b467e943.pdf">http://www1.cooperbusssmann.com/pdf/1d43a21b-d2a9-476a-8090-9972b467e943.pdf</a> |
|-------------------------|---|