



Eaton 5SC 2200i RT2U

Part no. Eaton 5SC 2200i RT2U
 Catalog No. 5SC2200IRT

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecI@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	184 - 276
Primary frequency	Hz	47 - 70
Number of phases primary		1
Output voltage	V	220 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	1980
Output apparent power	VA	2200
Type of interface		Other
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	86
Width	mm	440
Depth	mm	522
Transition time for full load	min	4.6
Weight	kg	26.5
Network-management		No
USV- technology		Line-interactive
Construction type		482.6 mm (19 inch) device
Max. voltage distortion output (linear load)	%	25
Output power factor		0.9
Overall efficiency	%	70
Efficiency in eco-mode	%	95.8
Potential free switch contact		Yes
Auto shut down function		Yes
Input connection		C14
Number of output connections C13		8
Number of output connections C19		1
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		0