



**Oil fuse-link, medium voltage, 20 A, AC 7.2 kV, BS2692 F01, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker**

**Catalog No. 7.20EFMA20**

Similar to illustration

### Delivery program

|                              |   |    |   |
|------------------------------|---|----|---|
| Product range                |   |    | Fuse  |
| Basic function               |   |    | Oil fuse-link   |
| Field of application         |   |    | medium voltage  |
| Rated current                | I | A  | 20  |
| Rated voltage                |   |    | AC 7.2 kV   |
| Construction size            |   |    | BS2692 F01  |
| Size                         |   |    | 254 x 63.5 mm   |
| Utilization category         |   |    | back-up   |
| Status indicator             |   |    | with striker  |
| Description                  |   |    | oil-tight   |
| Breaking Capacity            |   | kA | 45  |
| usable for size/applications |   |    | protection of primary side transformer, and oil-filled fuse switch combination unit |
| Standard/Approval            |   |    | BS<br>IEC<br>ESI  |
| Shape                        |   |    | cylindrical   |
| Standards/Regulations        |   |    | BS2692-1<br>IEC 60282-1<br>ESI 12-8   |

### Technical data ETIM 7.0

|  |  |    |                                     |
|--|--|----|-------------------------------------|
| Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) |  |    |                                     |
| Rated current  |  | A  | 20                                  |
| Rated voltage  |  | kV | 7.2                                 |
| Voltage type   |  |    | AC                                  |
| Rated frequency  |  | Hz | 50 - 50                             |
| Breaking capacity  |  | kA | 45                                  |
| Utilization category   |  |    | Other                               |
| Application  |  |    | Primary side transformer protection |
| Length   |  | mm | 254                                 |
| Diameter   |  | mm | 63.5                                |
| Performance category according to IEC 60282-1                                |  |    | Back-up                             |
| With striker   |  |    | Yes                                 |
| Standard   |  |    | British Standard                    |
| Release characteristic   |  |    | Other                               |
| Installation technique   |  |    | Oil                                 |

### Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (pdf) | <a href="http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf">http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf</a> |
|-------------------------|---|