



Fuse-link, low voltage, 80 A, AC 600 V, DC 250 V, 200 kA, HRCII-C, gL/gG, CSA



Powering Business Worldwide™

Part no. **80A BRUSH FUSE CANADA**
 Catalog No. **80K07CR**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	80
Rated voltage			AC 600 V DC 250 V
Construction size			HRCII-C
Utilization category			gL/gG
Breaking Capacity		kA	200
usable for size/applications			Cable protection
Standard/Approval			CSA
Shape			offset bolted tags
Standards/Regulations			CSA C22.2 BS88-2 IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	80
Rated voltage		V	600
Voltage type			AC
Rated switching capacity		kA	80
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_4131_HRC_Form_II.pdf
-------------------------	---