

Fuse-link, High Speed, 900 A, AC 690 V, 78 x 64 mm, gL/gG, BS, IEC



Part no. **900A 690V TYPE T FUSE**  
 Catalog No. **900F4M**

**Delivery program**

Product range			Fuse
Basic function			Fuse-link
Field of application			High Speed
Rated current	I	A	900
Rated voltage			AC 690 V
Size			78 x 64 mm
Utilization category			gL/gG
usable for size/applications			thyristor protection
Standard/Approval			BS IEC
Shape			Flush end contact
Standards/Regulations			BS88-4 IEC 60269-4

**Technical data ETIM 6.0**

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			Other
Nominal rated current		A	900
Nominal rated voltage		V	690
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None

**Additional product information (links)**

Product catalogue (pdf)	<a href="http://www1.cooperbusssmann.com/pdf/b71af154-6591-41c9-b787-14f8ac3f77d4.pdf">http://www1.cooperbusssmann.com/pdf/b71af154-6591-41c9-b787-14f8ac3f77d4.pdf</a>
-------------------------	---