



Eaton 9E 20000i XL

Part no.  
Catalog No.

Eaton 9E 20000i XL  
9E20KIXL

**Technical data ETIM 7.0**

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecI@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	110 - 276
Primary frequency	Hz	40 - 70
Number of phases primary		1
Output voltage	V	220 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	16000
Output apparent power	VA	20000
Type of interface		Other
Number of phases secondary		1
SNMP		Yes
Voltage type		AC
Height	mm	815.5
Width	mm	350
Depth	mm	706
Transition time for full load	min	0
Weight	kg	159.83
Network-management		Yes
USV- technology		Online
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	2
Output power factor		0.8
Overall efficiency	%	93
Efficiency in eco-mode	%	97
Potential free switch contact		Yes
Auto shut down function		Yes
Input connection		Fixed connection
Number of output connections C13		0
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		1