



Eaton 9SX 6000i, 6000 VA, 5400 W, Input: Hardwired, Tower,

Part no. Eaton 9SX 6000i
Catalog No. 9SX6KI

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	176 - 276
Primary frequency	Hz	40 - 70
Number of phases primary		1
Output voltage	V	200 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	5400
Output apparent power	VA	6000
Type of interface		Other
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	575
Width	mm	244
Depth	mm	542
Transition time for full load	min	6
Weight	kg	65.5
Network-management		No
USV- technology		Online
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	3
Output power factor		0.9
Overall efficiency	%	94
Efficiency in eco-mode	%	98
Potential free switch contact		Yes
Auto shut down function		Yes
Input connection		Other
Number of output connections C13		0
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		1