



Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 22 kW, 32A, 346-415V, Outlets: (6) C19



Catalog No. EBAB11

Similar to illustration

Delivery program

Mass configuration		No
SNMP		No
Circuit breaker		(6) single-pole
Number of outputs (other)		0
Number of outlets with earth pin		6
Number of Outputs C20		0
Num of Outputs PC (SCHUKO)		0
Fitted with:		Mounting material
Package contents		PDU mounting accessories Quickstart Safety Instructions
Over voltage category		2
Serial interface		No
Input voltage		346-415V
Ethernet interface		No
Outlet control		No
Form factor		0U (Vertical)
Frequency rating		50/60 Hz
Special features		IEC outlet eGrip plug retention: retains all standard IEC plugs Colour-coded outlet and branch circuits for simple load balancing Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection Low-profile form factor: 52mm wide x 53mm deep on most models 60 Degree C operating temperature Installation: Button mounting on rear & side + variable mounting system
Mounting direction		Vertical
Input connection		IEC-60309 32A 3Ph
Cord length		3m
Type		Rack PDU
Phase		Three-phase
Operating Temperature		0° to 60°C (32° to 140°F)
Outlets		6XC19
Number of Outputs C13		0
Number of Outputs C19		6
Amperage Rating		32A
ETIM Class		EC002762
Mounting dimension (standardized)		Metric
Electrical connection		Connecting cord with plug
Evaluation		Other
Mounting Dimension (metrical)		52
Switchable		No

Wattage		22 kW max
Color		Black

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)

Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])

Mounting dimension (standardised)		Metric
Mounting dimension	mm	
Mounting direction		Vertical
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		6
Number of C13 socket outlets		0
Number of C19 socket outlets		6
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		
Number of height units		
Length	mm	700
Width	mm	53
Height	mm	52
Depth	mm	700
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		No
With display		No
Evaluation		Other
With LED indication		No
With fuse		No
Ampere meter		No
With temperature measurement		No
With mounting material		Yes