



**Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 2XIEC60309 32A 3P**



**Catalog No. EILB26**

Similar to illustration

## Delivery program

Type			Rack PDU
Input Connection			2 x IEC-60309 32A 3Ph
Cord Length			3m
Input Voltage			346-415V
Phase			Three-phase
Frequency Rating			50/60 Hz
Ethernet Interface			Yes
Serial Interface			Yes
Form Factor			0U (Vertical)
Outlet Control			No
Operating Temperature			0° to 60°C (32° to 140°F)
Outlets			2XIEC60309 32A 3P
Number of Outputs C13			0
Number of Outputs C19			0
Amperage Rating			32A
Mounting Direction			Vertical
ETIM Class			EC002762
Fitted With:			Display Mounting material Ampere Meter
Electrical Connection			Connecting cord with plug
Evaluation			At distance
Mounting Dimension (metrical)			52
Mounting Dimension (standardised)			Metric
Switchable			No
Over Voltage Category			2
Wattage			22 kW max
Communication			HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP			Yes
Mass Configuration			Yes
Package Contents			PDU, Mounting accessories, Network cable, Configuration cable, Splitter for daisy-chaining, Quickstart guide, Safety Instructions
Number of Outputs C20			0
Num of Outputs PC (SCHUKO)			0
Number of Outputs (Other)			2
Number of Outlets with Earth Pin			2
Color			Black

## Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ec@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		Metric
Mounting dimension	mm	52
Mounting direction		Vertical
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		2
Number of C13 socket outlets		0
Number of C19 socket outlets		0
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		2
Number of height units		0
Length	mm	439
Width	mm	65
Height	mm	52
Depth	mm	439
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes