



Eaton Ellipse PRO 850 DIN

Part no. Eaton Ellipse PRO 850 DIN
Catalog No. ELP850DIN

Delivery program

Product range	UPS
---------------	-----

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	165 - 285
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	220 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	510
Output apparent power	VA	850
Type of interface		USB
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	260
Width	mm	82
Depth	mm	285
Transition time for full load	min	1
Weight	kg	7.3
Network-management		No
USV- technology		Line-interactive
Construction type		482.6 mm (19 inch) device
Max. voltage distortion output (linear load)	%	0
Output power factor		0.6
Overall efficiency	%	95
Efficiency in eco-mode	%	95
Potential free switch contact		No
Auto shut down function		Yes
Input connection		Protective contact (SCHUKO)
Number of output connections C13		0
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		4
Number of output connections fixed connection		0